NAME

mailstats − display mail statistics

SYNOPSIS

mailstats [**−o**] [**−p**] [**−C** *cffile*] [**−f** *stfile*]

DESCRIPTION

The **mailstats** utility displays the current mail statistics.

First, the time at which statistics started being kept is displayed, in the format specified by ctime(3). Then, the statistics for each mailer are displayed on a single line, each with the following white space separated fields:

M	The mailer number.
msgsfr	Number of messages from the mailer.
bytes_from	Kbytes from the mailer.
msgsto	Number of messages to the mailer.
bytes_to	Kbytes to the mailer.
msgsrej	Number of messages rejected.
msgsdis	Number of messages discarded.
Mailer	The name of the mailer.

After this display, a line totaling the values for all of the mailers is displayed (preceeded with a ‘‘T’’), separated from the previous information by a line containing only equals (‘‘=’’) characters. Another line preceeded with a ‘‘C’’ lists the number of connections.

The options are as follows:

−C Read the specified file instead of the default **sendmail** ‘‘cf’’ file.

−f Read the specified statistics file instead of the statistics file specified in the **sendmail** ‘‘cf’’ file.

−p Output information in program-readable mode and clear statistics.

−o Don’t display the name of the mailer in the output.

The **mailstats** utility exits 0 on success, and >0 if an error occurs.

FILES

/etc/mail/sendmail.cf	The default **sendmail** ‘‘cf’’ file.
/etc/mail/statistics	The default **sendmail** statistics file.

SEE ALSO

mailq(1), sendmail(8)